

SDYE、SDYH、SDYZ pressure sensor(SDYE、SDYH、SDYZ系列压力传感器)

Picture(图片)			
Type code(系列)	SDYE-XX	SDYH-P0	SDYZ-C1
Specification(性能参数)			
Pressure range(量程范围)	0-160MPa,0-200MPa	0-350KPa,Max0-100MPa	≥100MPa,Max250MPa
Pressure unit(压力单位)	K:KPa, M:MPa, B:bar, P:PSi		
Power supply(供电)	5V		
Output(输出类型)	0.5V-4.5V		
Shell material(壳体材质)	17-4PH stainless steel/17-4PH不锈钢	17-4PH/316L stainless steel/17-4PH/316L 不锈钢	
Pressure nipple(压力接口)	no O-ring sealing, no welding,no silicone oil,keep out leakage trouble/无O型圈,无焊接,无硅油,无泄漏隐患		
Connection(连接方式)	C1:1m cable(1m电缆线), P0 : packard connector(packard接头), XX:others(其它连接方式)		
Pipe size(接管口径)	M18:M18X1.5, G:G3/8, X:others(其它机械接口)		
Feature(产品特点)	High reliability, high overload capacity with internal buffer structure/高可靠性,高过载能力,内部缓冲结构		
Shape structure(外形结构)	Variety/外形结构多样化		
Application(典型应用)			
1	Specal for large diesel engine/大型柴油发动机专用		
2	Special for construction equipment/工程机械专用		
3	leakage detecting equipment/检漏仪器		
Dimension(尺寸图)	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>■ Connection XX</p> </div> <div style="text-align: center;"> <p>■ Connection P0</p> </div> </div> <p>Unit : mm</p>		