

产品特点(Product Features):

尺寸(Size):Φ92X92X25mm

构造(Construction):

- ▶ 铝合金压铸件(Die-cast Aluminum Housing)
- ▶ 玻璃纤维增强塑料叶轮UL 94V-0评级
(Glass Fiber Reinforced Plastic Impeller, UL 94V-0 Rating)
- ▶ 阻抗保护(Impedance Protected)
- ▶ 引线或终端是可用的(Leader Wire Or Terminal Is Available)

温度范围(Operating Temperature):

- ▶ 滚珠轴承(Ball Bearing) -30°C to +75°C
- ▶ 含油轴承(Sleeve Bearing) -10°C to +70°C

重量(Weight):

- ▶ 280grams



产品特性参数 Specification

MODEL	BEARING	RATING	FREQUENCY	RATING	POWER	SPEED	AIR FLOW		STATIC PRESSURE	NOISE
		VOLTAGE		CURRENT			CONSUMPTION	m ³ /min		
		VAC	Hz	A	W	RPM			mmH ₂ O	dB-A
9225B1H*	Ball	115	50/60	0.12/0.10	14.0/13.5	2550/2900	0.85/1.05	30/37	3.30/4.83	32/37
9225S1H*	Sleeve									
9225B1M*	Ball	115	50/60	0.09/0.08	11.0/10.0	2300/2600	0.71/0.85	25/30	3.00/3.50	25/33
9225S1M*	Sleeve									
9225B1L*	Ball	115	50/60	0.07/0.07	9.0/8.0	2000/2200	0.60/0.62	21/22	2.70/2.60	22/24
9225S1L*	Sleeve									
9225B2H*	Ball	220/240	50/60	0.07/0.06	14.0/13.5	2550/2900	0.85/1.05	30/37	3.30/4.83	32/37
9225S2H*	Sleeve									
9225B2M*	Ball	220/240	50/60	0.06/0.06	11.0/10.0	2300/2600	0.71/0.85	25/30	3.00/3.50	25/33
9225S2M*	Sleeve									
9225B2L*	Ball	220/240	50/60	0.05/0.05	9.0/8.0	2000/2200	0.60/0.62	21/22	2.70/2.60	22/24
9225S2L*	Sleeve									

*=T,L(T-Terminal type,L-Lead wire)

