

产品特点(Product Features):

尺寸(Size):Φ120X120X25mm

构造(Construction):

- ▶ 铝合金压铸件(Die-cast Aluminum Housing)
- ▶ 玻璃纤维增强塑料叶轮UL 94V-0评级
(Glass Fiber Reinforced Plastic Impeller, UL 94V-0 Rating)
- ▶ 阻抗保护(Impedance Protected)
- ▶ 引线或终端是可用的(Leader Wire Or Terminal Is Available)

温度范围(Operating Temperature):

- ▶ 滚珠轴承(Ball Bearing) -30°C to +75°C
- ▶ 含油轴承(Sleeve Bearing) -10°C to +70°C

重量(Weight):

- ▶ 380grams



产品特性参数 Specification

MODEL	BEARING	RATING	FREQUENCY	RATING	POWER	SPEED	AIR FLOW		STATIC	NOISE
		VOLTAGE	Hz	CURRENT	CONSUMPTION		m ³ /min	CFM	PRESSURE	
		VAC		A	W	RPM			mmH ₂ O	dB-A
12025B1H*	Ball	115	50/60	0.17/0.16	16.0/15.0	2200/2400	1.98/2.26	70/80	3.56/4.06	38/40
12025S1H*	Sleeve									
12025B1M*	Ball	115	50/60	0.16/0.15	13.0/12.0	2000/2000	1.76/1.76	62/62	3.00/3.20	35/35
12025S1M*	Sleeve									
12025B1L*	Ball	115	50/60	0.13/0.11	11.0/10.0	1800/1700	1.56/1.47	55/52	2.78/2.68	30/29
12025S1L*	Sleeve									
12025B2H*	Ball	220/240	50/60	0.09/0.09	16.0/15.0	2200/2400	1.98/2.26	70/80	3.56/4.06	38/40
12025S2H*	Sleeve									
12025B2M*	Ball	220/240	50/60	0.07/0.07	13.0/12.0	2000/2000	1.76/1.76	62/62	3.00/3.20	35/35
12025S2M*	Sleeve									
12025B2L*	Ball	220/240	50/60	0.05/0.05	11.0/10.0	1800/1700	1.56/1.47	55/52	2.78/2.68	30/29
12025S2L*	Sleeve									

*=T,L(T-Terminal type,L-Lead wire)

