

产品特点(Product Features):

尺寸(Size):Φ120X120X38mm

构造(Construction):

- ▶ 铝合金压铸件(Die-cast Aluminum Housing)
- ▶ 玻璃纤维增强塑料叶轮UL 94V-0评级
(Glass Fiber Reinforced Plastic Impeller, UL 94V-0 Rating)
- ▶ 阻抗保护(Impedance Protected)
- ▶ 引线或终端是可用的(Leader Wire Or Terminal Is Available)

温度范围(Operating Temperature):

- ▶ 滚珠轴承(Ball Bearing) -30°C to +75°C
- ▶ 含油轴承(Sleeve Bearing) -10°C to +70°C

重量(Weight):

- ▶ 530grams



产品特性参数 Specification

MODEL	BEARING	RATING	FREQUENCY	RATING	POWER	SPEED	AIR FLOW		STATIC	NOISE
		VOLTAGE	Hz	CURRENT	CONSUMPTION		m ³ /min	CFM	PRESSURE	
		VAC		A	W	RPM			mmH ₂ O	dB-A
12038B1H*	Ball	115	50/60	0.22/0.18	21.0/18.0	2650/2950	2.58/3.20	91/113	7.35/8.62	40/45
12038S1H*	Sleeve									
12038B1M*	Ball	115	50/60	0.17/0.15	16.0/14.0	2400/2200	2.10/2.00	75/70	5.60/5.00	37/35
12038S1M*	Sleeve									
12038B1L*	Ball	115	50/60	0.14/0.12	12.0/10.5	2000/1800	1.87/1.70	66/60	4.80/4.50	30/29
12038S1L*	Sleeve									
12038B2X*	Ball	220/240	50/60	0.14/0.12	22.0/21.0	2700/3100	2.68/3.25	95/115	8.38/9.65	42/47
12038S2X*	Sleeve									
12038B2H*	Ball	220/240	50/60	0.12/0.11	20.0/19.0	2650/2950	2.58/3.20	91/113	7.35/8.62	40/45
12038S2H*	Sleeve									
12038B2M*	Ball	220/240	50/60	0.09/0.08	16.0/14.0	2400/2200	2.10/2.00	75/70	5.60/5.00	37/35
12038S2M*	Sleeve									
12038B2L*	Ball	220/240	50/60	0.08/0.08	12.0/10.5	2000/1800	1.87/1.70	66/60	4.80/4.50	30/29
12038S2L*	Sleeve									
12038B3H*	Ball	380	50	0.07	18.0	2600	2.58	91	6.35	40
12038S3H*	Sleeve									
12038B3M*	Ball	380	50	0.06	16.0	2400	2.10	75	5.60	37
12038S3M*	Sleeve									
12038B3L*	Ball	380	50	0.05	12.0	2000	1.87	66	4.80	30
12038S3L*	Sleeve									

*=T,L(T-Terminal type,L-Lead wire)

