

产品特点(Product Features):

尺寸(Size): Φ 172X150X51mm

构造(Construction):

- ▶ 铝合金压铸件(Die-cast Aluminum Housing)
- ▶ 玻璃纤维增强塑料叶轮UL 94V-0评级
(Glass Fiber Reinforced Plastic Impeller, UL 94V-0 Rating)
- ▶ 阻抗保护(Impedance Protected)
- ▶ 引线或终端是可用的(Leader Wire Or Terminal Is Available)

温度范围(Operating Temperature):

- ▶ 滚珠轴承(Ball Bearing) -30°C to +75°C
- ▶ 含油轴承(Sleeve Bearing) -10°C to +70°C

重量(Weight):

- ▶ 908grams



产品特性参数 Specification

MODEL	BEARING	RATING	FREQUENCY	RATING	POWER	SPEED	AIR FLOW		STATIC	NOISE
		VOLTAGE	Hz	CURRENT	CONSUMPTION		m ³ /min	CFM	PRESSURE	
		VAC		A	W	RPM			mmH ₂ O	dB-A
15050B1H*	Ball	115	50/60	0.50/0.45	37.0/36.0	2600/3000	5.68/6.96	200/245	14.00/16.00	46/52
15050S1H*	Sleeve									
15050B1M*	Ball	115	50/60	0.41/0.39	32.0/30.0	2400/2300	5.06/4.72	178/166	12.00/11.00	43/42
15050S1M*	Sleeve									
15050B1L*	Ball	115	50/60	0.35/0.35	26.0/25.0	1900/1500	3.69/3.27	130/115	7.80/5.90	35/33
15050S1L*	Sleeve									
15050B2H*	Ball	220/240	50/60	0.22/0.21	34.0/33.0	2600/3000	5.68/6.96	200/245	14.00/16.00	46/52
15050S2H*	Sleeve									
15050B2M*	Ball	220/240	50/60	0.19/0.18	30.0/28.0	2400/2300	5.06/4.72	178/166	12.00/11.00	43/42
15050S2M*	Sleeve									
15050B2L*	Ball	220/240	50/60	0.16/0.16	26.0/25.0	1900/1500	3.69/3.27	130/115	7.80/5.90	35/33
15050S2L*	Sleeve									
15050B3H*	Ball	380	50	0.11	34.0	2600	5.68	200	14.00	46
15050S3H*	Sleeve									
15050B3M*	Ball	380	50	0.09	30.0	2400	5.06	178	12.00	43
15050S3M*	Sleeve									
15050B3L*	Ball	380	50	0.07	26.0	1900	3.69	130	7.80	35
15050S3L*	Sleeve									

*=T,L(T-Terminal type,L-Lead wire)

