

## 产品特点(Product Features):

尺寸(Size):Φ220X60mm

构造(Construction):

- ▶ 铝合金压铸件(Die-cast Aluminum Housing)
- ▶ 玻璃纤维增强塑料叶轮UL 94V-0评级  
(Glass Fiber Reinforced Plastic Impeller, UL 94V-0 Rating)
- ▶ 阻抗保护(Impedance Protected)
- ▶ 引线或终端是可用的(Leader Wire Or Terminal Is Available)

温度范围(Operating Temperature):

- ▶ 滚珠轴承(Ball Bearing) -30°C to +75°C

重量(Weight):

- ▶ 1400grams



## 产品特性参数 Specification

MODEL	BEARING	RATING	FREQUENCY	RATING	POWER	SPEED	AIR FLOW		STATIC	NOISE
		VOLTAGE	Hz	CURRENT	CONSUMPTION		m <sup>3</sup> /min	CFM	PRESSURE	dB-A
		VAC		A	W	RPM			mmH <sub>2</sub> O	
22060B1H*	Ball	115	50/60	0.76/0.77	57.0/58.0	2400	11.00	388	25.40	56
22060B1X*-TC	Ball	115	50/60	0.42/0.46	50.0/60.0	2800/3200	11.32/12.74	400/450	28.00/36.00	61/66
22060B2H*	Ball	220/240	50/60	0.28/0.29	40.0/38.0	2400	11.00	388	25.40	56
22060B2X*-TC	Ball	220/240	50/60	0.26/0.26	50.0/60.0	2800/3200	11.32/12.74	400/450	28.00/36.00	61/66
22060B3H*	Ball	380	50	0.16	40.0	2400	11.00	388	25.40	56

\*=T,L(T-Terminal type,L-Lead wire)

