



型号Model	M8-3F□L-02AY-* M8-4F□L-02CY-*		M8-3M□L-02AY-* M8-4M□L-02CY-*	
额定电压(最大电压) Rated voltage (maximum voltage)	3-Pin , 4-Pin , LED 60V ,30V, 24 VDC		3	60V
			4	30V
电流负荷(最大电流) Current load (maximum current)	3-Pin , 4-Pin 4A		3 , 4	4A
绝缘电阻 Insulation resistance	≥10 ⁸ Ω			
材质Material	压头Indenter		TPU(黑色,棕色等) .PP白色/TPU Black, Brown, etc.PP white	
	触头载体Contact carrier		PA(黑色,棕色等) .PP白色/PA Black, Brown, etc.PP white	
	密封圈Sealing ring		FPM/FKM	
	触点Contact point		铜锌 镀金Copper zinc. Gold plated	
	锁紧机构Locking mechanism		铜锌 镀镍.不锈钢Copper zinc. Nickel plated. Stainless steel	
环境温度 Ambient temperature	标准型 : -40°C/ +150°C (LED+110°C)			
防护等级 (拧紧状态) Protection level (tightened state)	IP67,IP69			
机械寿命周期 Mechanical cycle	>150拔插次数> 150 pull outs			
孔头 (母头) 编码 Hole(female connector)coding	1.棕色2.白色3.蓝色4.黑色 1. brown 2. white 3. blue 4. Black		1.棕色2.白色3.蓝色4.黑色 (粉红色) 1. brown 2. white 3. blue 4. Black(pink)	
排列图	<p>3针</p> <p>1:BN 3:BU 4:BK</p>	<p>4针</p> <p>1:BN 2:WH 3:BU 4:BK</p>	<p>3针</p> <p>1:BN 3:BU 4:BK</p>	<p>4针</p> <p>1:BN 2:WH 3:BU 4:BK</p>
Dimension(尺寸图)				